## NSN 5305-00-446-1598

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-446-1598 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.320 inches **Fastener Length:** 1.680 inches **Head Style:** Flat chamfer **Head Diameter:** 0.520 inches **Head Height:** 0.060 inches **Shoulder Diameter:** 0.375 inches first shoulder **Shoulder Length:** 0.188 inches first shoulder **Shank Unthreaded Hole Diameter:** 0.076 inches first hole **Internal Drive Style:** Slot **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Center: 0.170 inches first hole **Shoulder Shape:** Round first shoulder Material: Steel comp 4130 **Material Specification:** Mil-s-6758, physical cond. F, surface cond. 4 military specification single material response **Surface Treatment:** Cadmium **Thread Series Designator:** Unf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-00-446-1598

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.