## NSN 5305-00-446-9409

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-446-9409 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.658 inches and 0.750 inches **Fastener Length:** Between 0.720 inches and 0.750 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** Between 36.0 rockwell c and 40.0 rockwell c **Screw Material:** Steel **Screw Material Specification:** Mil-s-7839 military specification single material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Special Features:** Furnisher with one washer mil-p-17091, head and washer covered with black epoyy federal standard 595 no. 37038 **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-00-446-9409

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-7839 spec.