
Socket Head Cap Screw - Page 1 of 2





## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.422 inches and 0.516 inches Fastener Length: Between 0.484 inches and 0.516 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches Hole Diameter: 0.036 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.109 inches and 0.111 inches Hole Quantity: 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b **Minimum Yield Strength:** 30000 pounds per square inch Hole Configuration Style: Round internal hexagon Material: Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 Surface Treatment: Passivate **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response

## NSN 5305-00-447-7100

Socket Head Cap Screw - Page 2 of 2

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

