## NSN 5305-00-448-4225

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-448-4225 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.294 inches and 0.375 inches **Fastener Length:** Between 0.344 inches and 0.375 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.058 inches and 0.068 inches **Locking Feature:** Pellet threads **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 90000 pounds per square inch **Criticality Code Justification:** Cqbc Material: Steel comp 304 or steel comp 316 or steel comp 303se or steel comp 316l or steel comp 305 or steel comp 303 or steel comp 302 or steel **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Test Data Document:** 01714-g395885 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Thread Series Designator:** Unc Shelf Life: N/a

No

**Unit Of Measure:** 

**Demilitarization:** 

## NSN 5305-00-448-4225

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0