NSN 5305-00-448-4707

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-448-4707 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.346 inches and 0.386 inches **Fastener Length:** Between 0.428 inches and 0.448 inches **Head Style:** Double hexagon **Head Height:** 0.230 inches Width Between Flats: 0.219 inches **Extended Washer Diameter:** 0.312 inches **Extended Washer Thickness:** 0.030 inches **First Diameter From Head:** Between 0.141 inches and 0.151 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.062 inches and 0.082 inches **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 36 Min. Tensile Strength (psi): 130000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-00-448-4707

Externally Relieved Body Screw - Page 2 of 2



| _ | | •• | • • | | | | |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш | 112 | rız | 211 | n | ٠. |
| | | | | | | | |

No

Fiig:

A003b0