## NSN 5305-00-448-6456

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-448-6456 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.532 inches and 0.625 inches **Fastener Length:** Between 0.594 inches and 0.625 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch **Screw Material:** Stainless steel or steel **Screw Material Specification:** Qq-s-763, 300 series federal specification 1st material response or 66, 300 series federal standard 1st material response or comp 16-18 or 18-8 assn standard 2nd material response **Screw Surface Treatment:** Oxide **Screw Surface Treatment Specification:** Mil-c-13924 cl 4 military specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 3 type and 9c style Shelf Life: N/a **Unit Of Measure:** 

Fiig: A500d0

No

**Demilitarization:** 

## NSN 5305-00-448-6456

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-13924 spec.