

View Online at <https://aerobasegroup.com/nsn/5305-00-448-6590>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.541 inches and 0.634 inches

Fastener Length:

Between 0.719 inches and 0.750 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.340 inches and 0.385 inches

Internal Drive Style:

Cross recess type 1

End Application:

Medium mine protected vehicle - mmpv

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

80000 pounds per square inch

Countersink Angle:

Between 80.0 degrees and 82.0 degrees

Screw Material:

Stainless steel

Screw Material Specification:

Qq-s-763 federal specification 1st material response or federal standard no. 66 federal standard 2nd material response or 16-18 assn standard 3rd material response or 18-8 assn standard 4th material response

Screw Surface Treatment:

Oxide

Screw Surface Treatment Specification:

Mil-c-13924 cl 4 military specification single treatment response

Thread Series Designator:

Unf

Specification Or Standard:

3 type and 2c style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0

Mil-std (military Standard):

Mil-c-13924 spec.