NSN 5305-00-448-7366

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-448-7366 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.188 inches **Fastener Length:** Between 0.406 inches and 0.438 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.191 inches and 0.225 inches First Diameter From Head: 0.112 inches **Second Diameter From Head:** Between 0.070 inches and 0.080 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.110 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.218 inches and 0.250 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc

Shelf Life:

Onch En

N/a

NSN 5305-00-448-7366

Externally Relieved Body Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0