Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-448-7366

Thread Class:
2a
Za Thread Direction:
Right-hand
Thread Length:
0.188 inches
Fastener Length:
Between 0.406 inches and 0.438 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.191 inches and 0.225 inches
First Diameter From Head:
0.112 inches
Second Diameter From Head:
Between 0.070 inches and 0.080 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
0.110 inches
Distance From Largest Bearing Surface Of Head To End Of Second Diameter:
Between 0.218 inches and 0.250 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.112 inches
Thready Qty Per Inch (tpi):
40
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Externally Relieved Body Diameter Quantity:
2
Material:
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316
Material Specification:
66 federal standard all material responses
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a

Externally Relieved Body Screw - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0