## NSN 5305-00-449-2563

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-449-2563 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 1.043 inches and 1.167 inches **Fastener Length:** Between 1.188 inches and 1.250 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.244 inches and 0.279 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Screw Material:** Stainless steel **Screw Material Specification:** Fed standard no. 66 federal standard 1st material response or 16-18 assn standard 2nd material response **Screw Surface Treatment:** Oxide **Screw Surface Treatment Specification:** Mil-c-13924 cl 1 military specification 1st treatment response or f-33 cl 2 fscm 96214 mfr ref 2nd treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

Mil-std (military Standard): Mil-c-13924 spec.

A500d0