Socket Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-450-0203

Bai Financian Riphtan Financian Financian <td< th=""><th>Thread Class:</th></td<>	Thread Class:
Right-hand Right-hand Right-hand Right-hands	3a
InselPresencePasse	Thread Direction:
6491 inches Fischer Longth: 1983 inches Had Syle: Fischamfer Batwen 0.550 inches and 0.562 inches Batwen 0.550 inches and 0.562 inches Had Haffe: Batwen 0.358 inches and 0.575 inches Internal Drive Syle: Hasagn Ministry Syle: 1000 pointer: 0.312 inches 1014 cross Flats: 0.321 inches 1020 pointer square inch 10200 pointel square inch 10300 pointel square inch 10300 pointel square inch 10300 pointel square inch 10300 pointel sengineering type bulletins, brochures, etc., fratreflect specification type data in specification formatic 10300 pointel sengineering type bulletins, brochures, etc., fratreflect specification type data in specification formatic 10300 pointer square inch 103000 pointel sengineering type bulletins, brochures, etc., fratreflect specification type data in specification formatic 10300 pointel sengineering type bulletins, brochures, etc., fratreflect specification type data in specification formatic 1040 formatic: International type data in test conditions that are shown as "typical", 'average", '', etc.). 1041 formatin: Internal type d	Right-hand
Faster Length: 1938 incles 1943 incles Hatchamker Fatchamker Beaton 0.550 inches and 0.562 inches Hatdlight: Beaton 0.550 inches and 0.375 inches Beaton 0.550 inches and 0.375 inches Beaton 0.550 inches and 0.375 inches Harad Drive Style: Assagn Thread Diameter: 0.375 inches 2045 inches 1037 inches Pathenes 0.375 inches 1037 inches 1038 inches and 0.375 inches 1038 inches 1037 inches 1038 inches 1037 inches 1037 inches 1038 inches 1037 inches 1038 inches 1037 inches 1038 inches 1039 inches 10300 pounds per square inch Hardness Rating: 10300 pounds per square inch 10400 pounds per square inch	Thread Length:
1953 inches Pist chamfer Head Diameter: Between 0.550 inches and 0.562 inches Head Diameter: Between 0.550 inches and 0.575 inches Heard Diameter: Between 0.550 inches and 0.375 inches Heard Diameter: Others of District Style: Herrad District Style: Horsen Dirts 0.375 inches Width Across Flat: 0.312 inches Theread Other Style: 100000 pounds per square inch Hortense Stating: 30.0 rockwell o and 450 rockwell o Mintensile Strength (ps): 100000 pounds per square inch Harden: 24 Mintense Stating: 30.0 rockwell o and 450 rockwell o Mintense Stating: 100000 pounds per square inch Harden: 250 rockwell o and 450 rockwell o Mintense Stating: 100000 pounds per square inch Harden: 260 rockwell o and 50 rockwell o Mintense Stating: 10000 pounds per square inch Harden: 10000 pounds per square i	0.641 inches
Had Style: Fita chamfar Hat Alpineter: Batween 0.550 inches and 0.552 inches Hael Height: Batween 0.350 inches and 0.375 inches Interal Drive Style: Haxagon Thread Dimeter: 0.375 inches Mitter Dimeter: 0.375 inches Vict Across Flats: 0.312 inches Mitter Dimeter: 0.312 inches Mitter Strength (psl): 1300 pounds per square inch Hardense Rating: 0.300 pounds per square inch Hardense Rating: 1300 pounds per square inch Minimum Yield Strength: 1300 pounds per square inch Bates Materia: 1300 pounds per square inch Materia: 1300 pounds per square inch Hateria: 1312 mm Heid Strength: 1300 pounds per square inch Hateria: 1300 pounds per square inch Hateria: 140 beta bacoument: 141 beta bacoument: 141 beta bacoument: 142 bet	Fastener Length:
Fact duranter Read Obsention: Readen 0.550 inches and 0.562 inches Head Height: Between 0.580 inches and 0.375 inches Isternal Drive Style: Isternal Drive Style: Isternal Drive Style: 10375 inches Victh Access Flas: 0.375 inches Victh Access Flas: 0.375 inches Mintersite Strength (psi): 10000 pounds per square inch Hardness Rating: 10000 pounds per square inch 100	1.953 inches
Had Dancier: Retween 0.550 inches and 0.562 inches Heldleitt: Retween 0.580 inches and 0.375 inches Bitteren 0.388 inches and 0.375 inches Harda Dinnetier: Retagon Thread Diameter: 0.375 inches Vicht Across Flats: 0.312 inches Hardnets Statign: 10000 pounds per square inch Hardnets Statign: 10200 pounds per square inch Hardnets Statign: 10300 pounds per square inch Hardnets Statign: 10300 pounds per square inch 10300 pounds p	Head Style:
Between 0.550 inches and 0.562 inches Head Height: Between 0.385 inches and 0.375 inches Interal Drive Style: Hexagon Tread Dimeter: 0.375 inches With Across Flats: 0.312 inches Tread Drive Style: 0.312 inches Mint Const Flats: 0.312 inches Mint Const Flats: 0.312 inches Mint Const Strength (psi): 124 Mint Const Strength (psi): 130000 pounds per square inch Hardense Rating: 130000 pounds per square inch Metril: 130000 pounds per square inch Bate-Inities 130000 pounds per square inch Bate-Inities 130000 pounds per square inch Bate-Inities 130000 pounds per square inch Interal Decement: 13149-milies88 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental aperformance requirements and test conditions that are shown as "typical", "average", "", etc.). Inter State Document: Int of Measure: Int of Measure:	Flat chamfer
Had Height: Between 0.388 inches and 0.375 inches Herwal Drive Style: Hexagon Thread Dameter: 0.375 inches Vall Across Flats: 0.372 inches Thread Qty Per Inch (pt): 24 Min Tensile Strength (psi): 160000 pounds per square inch Hondensker: 130000 pounds per square inch Hondensker: 130000 pounds per square inch Hondensker: 130000 pounds per square inch Haterial: 130000 pounds per square inch Hateria: 130000 pounds per square inch 130000 pounds per square inch 130000 pounds pe	Head Diameter:
Betwen 0.388 inches and 0.375 inches Iternal Drive Style: Hexagon Thread Diameter: 0.375 inches Width Across Flats: 0.312 inches Thready Qry Per Inch (tpi): 24 Incensile Strength (psi): 160000 pounds per square inch Horiness Ratting: 30.00 pounds per square inch Minimum Yield Strength: 130000 pounds per square inch Marcias: 150000 pounds per square inch 160000 pounds per square inch 170000 pounds per square inch 18149-mili6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: 18149-mili6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: 18149-mili6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: 18149-mili6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental 18149-mili6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental 18149-mili6868 specification (includes engineering ty	Between 0.550 inches and 0.562 inches
Interal Drive Style: Hexagon Interal Diameter: 0.375 Inches With Across Flats: 0.312 Inches Interal Origination 0.312 Inches Interal Origination 10312 Inches Interact Origination 0.312 Inches Interact Origination 10300 pounds per square Inch 16000 pounds per square Inch Horness Ratting: 10000 pounds per square Inch 10000 pounds per square Inch <	Head Height:
Hexagon Inread Diameter: 0.375 Inches With Across Flats: 0.312 Inches Thready Quy Per Inch (tpi): 24 Inrensile Strength (psi): 140000 pounds per square inch Hardness Rating: 0.300 rokwell c and 45.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Material: 130000 pounds per square inch 149 HildsB68 specification (includes engineering type bulletins, brochures, efc., that reflect specification type data in specification format: 140 Hered Strength: Thered Strength:	Between 0.368 inches and 0.375 inches
Incerd Diameter: 0.375 inches Vidth Across Flats: 0.312 inches Thready Gty Per Inch (tpi): 24 Inssile Strength (psi): 160000 pounds per square inch Hardness Rating: 26.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 30000 pounds per square inch Hardness Rating: 130000 pounds per square inch Material: Steel 1512 15134 Document: 81349-mili6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formants; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental	Internal Drive Style:
 0.375 inches 0.375 inches 0.312 inches<	Hexagon
With Across Flats: 0.312 inches Incady Qty Per Inch (tpi): 24 Inf. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 0.302 rockwell c and 45.0 rockwell c Minnum Yield Strength 13000 pounds per square inch Materiation 13000 pounds per square inch Minnum Yield Strength: 13000 pounds per square inch Materiation 13000 pounds per square inch Materiation 13000 pounds per square inch Steel Steel Particite Steelification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "etc.). Fired Series Designato: Ivid Int of Measure: - Int of Measure: - Int of Measure: Ivid Intervection: Ivid Intervection: Ivid Intervection:	Thread Diameter:
0.312 inches Inready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 0.302 nockwell c and 45.0 rockwell c Minnum Yield Strength: 130000 pounds per square inch Material: 3000 pounds per square inch Material: Steel Part Data Document: 81349-mili6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Hread Series Designator: Vaf Material: Na Intio Measure: - Intio Measure: - Intiltarization: Na Discussion: Na Discussion: Intiltarization: Intiltarization: Intiltarization: Intiltarization: Intiltarization: Intiltaris to int	0.375 inches
Inready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Material: Stel B1349-mili6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: adperformance requirements and test conditions that are shown as "typical", "average", "", etc.). Interformance requirements and test conditions that are shown as "typical", "average", "", etc.). Interformance requirements and test conditions that are shown as "typical", "average", "", etc.). Interformance requirements and test conditions that are shown as "typical", "average", "", etc.). Interformance requirements and test conditions that are shown as "typical", "average", "", etc.). Interformance requirements and test conditions that are shown as "typical", "average", "", etc.). Interformance requirements and test conditions that are shown as "typical", "average", "", etc.). Interformance requirements and test conditions that are shown as "typical", "average", "", etc.). Interformance requirements and test conditions that are shown as "typical", "average", "", etc.). Interformance requirements and test conditions that are shown as "typical", "average", "", etc.	Width Across Flats:
24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Material: Steel Test Data Document: 81349-mill6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "*, etc.). Hread Series Designator: Ivit Main Ivit	0.312 inches
 kin. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Material: Steel Test Data Document: 81349-mili6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Ivia Shelf Life: Na Int Of Measure: - Imilitarization: No Fig: 	Thready Qty Per Inch (tpi):
160000 pounds per square inch Hardness Rating: 36.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Material: Steel Test Data Document: 81349-mili6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental an performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unf Shelf Life: Na Unit Of Measure: - Demilitarization: No Fig:	24
 Hardness Rating: 36.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 30000 pounds per square inch Material: Steel Test Data Document: Als9-mili6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; a veludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental an performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unf Shelf Life: N/a Int Of Measure: - militarization: No Fig: 	Min. Tensile Strength (psi):
36.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Material: Steel Test Data Document: 81349-mili6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unf Shelf Life: Na Int Of Measure: - Demilitarization: No Fig:	160000 pounds per square inch
 kinimum Yield Strength: 30000 pounds per square inch Material: Steel Test Data Document: 81349-mili6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unf Shelf Life: N/a Int Of Measure: - Demilitarization: No Fig: 	Hardness Rating:
 130000 pounds per square inch Material: Steel Test Data Document: 81349-mili6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig: 	36.0 rockwell c and 45.0 rockwell c
Material: Steel Test Data Document: 81349-mill6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	Minimum Yield Strength:
Steel Test Data Document: 81349-mili6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unf Shelf Life: N/a Uni Of Measure: - Demilitarization: No Fig:	130000 pounds per square inch
Fest Data Document: 81349-mili6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unf Shelf Life: N/a Init Of Measure: Demilitarization: No Fig:	Material:
 81349-mili6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: 	Steel
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	81349-mili6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Unf Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
N/a Unit Of Measure: Demilitarization: No Fiig:	
Unit Of Measure: Demilitarization: No Fiig:	
 Demilitarization: No Fiig:	
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	
A003b0	
	A003b0