NSN 5305-00-450-4084

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-450-4084

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| |
| Right-hand Thread Longth |
| Thread Length: |
| Between 0.423 inches and 0.473 inches |
| Fastener Length: |
| Between 1.308 inches and 1.338 inches |
| Head Style: |
| Flat countersunk Lead Biometers |
| Head Diameter: |
| Between 0.531 inches and 0.558 inches |
| Grip Diameter: |
| Between 0.3110 inches and 0.3120 inches |
| Internal Drive Style: |
| Offset cruciform (torque set) |
| Thread Diameter: |
| 0.312 inches |
| Grip Length: |
| Between 0.865 inches and 0.885 inches |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 220000 pounds per square inch |
| Countersink Angle: |
| Between 59.75 degrees and 60.25 degrees |
| Surface Finish: |
| 32.0 microinches threads |
| Special Features: |
| Bearing surface of head to be grooved to 0.394 in. Min 0.396 in. Maximum dia, 0.092 in. Min 0.097 in. Maximum from top of head |
| Material: |
| Steel comp h11 |
| Material Specification: |
| Ams6485 assn standard single material response |
| Surface Treatment: |
| Nickel and cadmium |
| Surface Treatment Specification: |
| Ams 2416 assn standard all treatment responses |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |

NSN 5305-00-450-4084

Close Tolerance Screw - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A003b0