NSN 5305-00-450-4084

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-450-4084

Thread Class:
3a
Thread Direction:
Right-hand Thread Longth
Thread Length:
Between 0.423 inches and 0.473 inches
Fastener Length:
Between 1.308 inches and 1.338 inches
Head Style:
Flat countersunk Lead Biometers
Head Diameter:
Between 0.531 inches and 0.558 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.312 inches
Grip Length:
Between 0.865 inches and 0.885 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Countersink Angle:
Between 59.75 degrees and 60.25 degrees
Surface Finish:
32.0 microinches threads
Special Features:
Bearing surface of head to be grooved to 0.394 in. Min 0.396 in. Maximum dia, 0.092 in. Min 0.097 in. Maximum from top of head
Material:
Steel comp h11
Material Specification:
Ams6485 assn standard single material response
Surface Treatment:
Nickel and cadmium
Surface Treatment Specification:
Ams 2416 assn standard all treatment responses
Thread Series Designator:
Unjf
Shelf Life:
N/a

NSN 5305-00-450-4084

Close Tolerance Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0