NSN 5305-00-450-5978

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-450-5978



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.773 inches and 0.875 inches Fastener Length: Between 0.844 inches and 0.875 inches Head Style: Flat chamfer **Head Diameter:** Between 0.367 inches and 0.375 inches **Head Height:** Between 0.133 inches and 0.150 inches Hole Diameter: 0.064 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.250 inches **Hole Quantity:** 2 Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 140000 pounds per square inch Hardness Rating: Between 248.0 brinell standard and 341.0 brinell standard **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams 5732 assn standard single material response **Screw Surface Treatment:** Passivate **Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response Head Hole Configuration Style: Round **Thread Series Designator:** Unjf Shelf Life: N/a

NSN 5305-00-450-5978

Machine Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A500d0

