## NSN 5305-00-450-6407

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-450-6407 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.380 inches **Fastener Length:** 1.830 inches **Head Style:** Flat chamfer **Head Diameter:** 0.180 inches **Head Height:** 0.100 inches **First Diameter From Head:** 0.090 inches **Second Diameter From Head:** 0.112 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.060 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 1.830 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 303se **Material Specification:** Qq-s-763 federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** 

Mil-f-14072e300 military specification all treatment responses

## **Test Data Document:**

98230-0n118815-3 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## **Thread Series Designator:**

Unc

## NSN 5305-00-450-6407

Externally Relieved Body Screw - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
No Fiig:

Mil-f-14072e300 spec.

Mil-std (military Standard):