NSN 5305-00-450-7446

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-450-7446 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.332 inches and 0.399 inches **Fastener Length:** Between 1.280 inches and 1.327 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.625 inches and 0.635 inches **Grip Diameter:** Between 0.3108 inches and 0.3117 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.928 inches and 0.948 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 300000 pounds per square inch Hardness Rating: 55.0 rockwell c and 58.0 rockwell c **Countersink Angle:** 100.0 degrees Surface Finish: 32.0 microinches threads Material: Vanadium alloy **Material Specification:** Vanadium alloy m-a, vanadium alloys steel co mfr ref single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams 2416 assn standard all treatment responses **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5305-00-450-7446

Close Tolerance Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0