NSN 5305-00-450-7459

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-450-7459 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.350 inches and 0.400 inches **Fastener Length:** Between 0.422 inches and 0.452 inches **Head Style:** Fillister **Head Diameter:** Between 0.429 inches and 0.438 inches **Head Height:** Between 0.162 inches and 0.183 inches **Hole Diameter:** 0.064 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.052 inches and 0.072 inches **Hole Quantity:** 2 **Hole Type:** Drilled Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 140000 pounds per square inch **Hardness Rating:** 248.0 brinell standard and 341.0 brinell standard **Hole Configuration Style:** Round **Surface Finish:** 32.0 microinches threads Material: Iron alloy 660

Material Specification:

Ams 5732 assn standard single material response

NSN 5305-00-450-7459

Close Tolerance Screw - Page 2 of 2



Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0