NSN 5305-00-451-6472

Setscrew - Page 1 of 2

Thread Class:

Test Data Document:



View Online at https://aerobasegroup.com/nsn/5305-00-451-6472

| 3a |
|---------------------------------------|
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.500 inches |
| Fastener Length: |
| 1.000 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| 0.250 inches |
| Head Height: |
| 0.200 inches |
| Hole Diameter: |
| 0.046 inches |
| Point Length: |
| 0.300 inches |
| Point Diameter: |
| Between 0.247 inches and 0.249 inches |
| Point Style: |
| Chamfer dog |
| Internal Drive Style: |
| Slot |
| Thread Diameter: |
| 0.375 inches |
| Hole Quantity: |
| 2 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 125000 pounds per square inch |
| Hole Configuration Style: |
| Round |
| Point Chamfer Angle: |
| 45.0 degrees |
| Material: |
| Steel comp 4130 |

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5305-00-451-6472

Setscrew - Page 2 of 2



| Thread Series Designator: |
|---------------------------|
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A003b0