NSN 5305-00-453-5584



Thumbscrew - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-453-5584 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 1.500 inches **Fastener Length:** 1.875 inches **Head Style:** Thumb no. 7 **Head Height:** 0.500 inches Width Between Flats: 2.000 inches **Shoulder Diameter:** 0.375 inches **Shoulder Length:** 0.380 inches **Point Style:** Flat **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 16 **Shoulder Shape:** Round fourth hole **Special Features:** Drilled hole in shank 0.078 in. Min, 0.081 in. Maximum diameter 0.375 in. From bearing surface of head. Other drilledhole in shank 0.076 in. Dia, 1.719 in. From bearing surface of head Material: Steel **Material Specification:** Mil-s-13048 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2 class 3 federal specification single treatment response **Thread Series Designator:**

Shelf Life:

N/a

Unc

Unit Of Measure:

NSN 5305-00-453-5584

Thumbscrew - Page 2 of 2



_										
וו	0	m	ш	м	2	iza	31	^	n	

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-13048 spec.