## NSN 5305-00-454-0313

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-454-0313 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.750 inches **Fastener Length:** Between 0.970 inches and 1.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.176 inches and 0.183 inches **Head Height:** Between 0.108 inches and 0.112 inches **Locking Feature:** Patch threads or pellet threads or strip threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.112 inches Width Across Flats: Between 0.094 inches and 0.095 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel fastener **Material Specification:** 66 federal standard single material response **Surface Treatment:** Cadmium fastener and chromate fastener **Surface Treatment Specification:** Qq-p-416. Type 2 class 2 federal specification single treatment response fastener **Thread Series Designator:** Unc Shelf Life: N/a

## NSN 5305-00-454-0313

Socket Head Cap Screw - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0