NSN 5305-00-454-0334

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-454-0334 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.422 inches and 0.516 inches **Fastener Length:** Between 0.484 inches and 0.516 inches **Head Style: Button Head Diameter:** Between 0.347 inches and 0.361 inches **Head Height:** Between 0.091 inches and 0.101 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.125 inches and 0.127 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Material: Steel **Material Specification:** 66 federal standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator: Specification Or Standard:**

Unf 8 type Shelf Life: N/a

NSN 5305-00-454-0334

Socket Head Cap Screw - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A003b0