NSN 5305-00-455-0382



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-455-0382 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.316 inches **Fastener Length:** Between 1.081 inches and 1.111 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.490 inches and 0.510 inches **Head Height:** Between 0.080 inches and 0.090 inches **Shoulder Diameter:** 0.3712 inches second shoulder and 0.3717 inches second shoulder **Shoulder Length:** 0.270 inches second shoulder and 0.295 inches second shoulder **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.086 inches first hole **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 0.965 inches first hole and 0.995 inches first hole **Shoulder Shape:** Round all shoulders **Special Features:** Shoulder 16 microinch finish Material: Steel comp h11 **Surface Treatment:** Cadmium

Unjf

Shelf Life:

Thread Series Designator:

N/a

NSN 5305-00-455-0382

Shoulder Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0