## NSN 5305-00-455-0442

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-455-0442 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.187 inches **Fastener Length:** 0.688 inches **Head Style:** Knurled no. 2 **Head Diameter:** 0.312 inches **Head Height:** Between 0.110 inches and 0.140 inches **First Diameter From Head:** Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.376 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Point style 6 0.095 in. Dia, 0.125 in. Lg by 60 degrees of angle Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-00-455-0442

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.