## NSN 5305-00-455-3319

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-455-3319

Thread Direction: Right-hand Thread Length: Between 0.657 inches and 0.750 inches Fastener Length: Between 0.719 inches and 0.750 inches Head Style: Fillister Head Diameter: Between 0.292 inches and 0.313 inches Head Height: Between 0.123 inches and 0.130 inches Internal Drive Style: Slot Thread Diameter: 0.190 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 62000 pounds per square inch Screw Material: Aluminum alloy 2024 Screw Material Specification: Qq-a-225/6 federal specification single material response Screw Surface Treatment: Anodize Screw Surface Treatment Specification: Mil-a-8625 military specification single treatment response Head Hole Configuration Style: Round
Right-hand Thread Length: Between 0.657 inches and 0.750 inches Fastener Length: Between 0.719 inches and 0.750 inches Head Style: Fillister Head Diameter: Between 0.292 inches and 0.313 inches Head Height: Between 0.123 inches and 0.130 inches Internal Drive Style: Slot Thread Diameter: 0.190 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 62000 pounds per square inch Screw Material: Aluminum alloy 2024 Screw Material Specification: Qq-a-225/6 federal specification single material response Screw Surface Treatment: Anodize Screw Surface Treatment Specification: Mil-a-8625 military specification single treatment response Head Hole Configuration Style: Round
Thread Length: Between 0.657 inches and 0.750 inches Fastener Length: Between 0.719 inches and 0.750 inches Head Style: Fillister Head Diameter: Between 0.292 inches and 0.313 inches Head Height: Between 0.123 inches and 0.130 inches Internal Drive Style: Slot Thread Diameter: 0.190 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 62000 pounds per square inch Screw Material: Aluminum alloy 2024 Screw Material Specification: Qq-a-225/6 federal specification single material response Screw Surface Treatment: Anodize Screw Surface Treatment Specification: Mil-a-8625 military specification single treatment response Head Hole Configuration Style: Round
Between 0.657 inches and 0.750 inches  Fastener Length:  Between 0.719 inches and 0.750 inches  Head Style:  Fillister  Head Diameter:  Between 0.292 inches and 0.313 inches  Head Height:  Between 0.123 inches and 0.130 inches  Internal Drive Style:  Slot  Thread Diameter:  0.190 inches  Hole Quantity:  1  Thready Qty Per Inch (tpi):  32  Min. Tensile Strength (psi):  62000 pounds per square inch  Screw Material:  Aluminum alloy 2024  Screw Material Specification:  Qq-a-225/6 federal specification single material response  Screw Surface Treatment:  Anodize  Screw Surface Treatment Specification:  Mil-a-8625 military specification single treatment response  Head Hole Configuration Style:  Round
Fastener Length: Between 0.719 inches and 0.750 inches Head Style: Fillister Head Diameter: Between 0.292 inches and 0.313 inches Head Height: Between 0.123 inches and 0.130 inches Internal Drive Style: Slot Thread Diameter: 0.190 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 62000 pounds per square inch Screw Material: Aluminum alloy 2024 Screw Material Specification: Qq-a-225/6 federal specification single material response Screw Surface Treatment: Anodize Screw Surface Treatment Specification: Mil-a-8625 military specification single treatment response Head Hole Configuration Style: Round
Between 0.719 inches and 0.750 inches  Head Style: Fillister  Head Diameter: Between 0.292 inches and 0.313 inches  Head Height: Between 0.123 inches and 0.130 inches  Internal Drive Style: Slot  Thread Diameter: 0.190 inches  Hole Quantity: 1  Thready Qty Per Inch (tpi): 32  Min. Tensile Strength (psi): 62000 pounds per square inch  Screw Material: Aluminum alloy 2024  Screw Material Specification: Qq-a-225/6 federal specification single material response  Screw Surface Treatment: Anodize  Screw Surface Treatment Specification: Mil-a-8625 military specification single treatment response  Head Hole Configuration Style: Round
Head Style: Fillister Head Diameter: Between 0.292 inches and 0.313 inches Head Height: Between 0.123 inches and 0.130 inches Internal Drive Style: Slot Thread Diameter: 0.190 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 62000 pounds per square inch Screw Material: Aluminum alloy 2024 Screw Material Specification: Qq-a-225/6 federal specification single material response Screw Surface Treatment: Anodize Screw Surface Treatment Specification: Mil-a-8625 military specification single treatment response Head Hole Configuration Style: Round
Fillister  Head Diameter:  Between 0.292 inches and 0.313 inches  Head Height:  Between 0.123 inches and 0.130 inches  Internal Drive Style:  Slot  Thread Diameter: 0.190 inches  Hole Quantity: 1  Thready Qty Per Inch (tpi): 32  Min. Tensile Strength (psi): 62000 pounds per square inch  Screw Material: Aluminum alloy 2024  Screw Material Specification: Qq-a-225/6 federal specification single material response  Screw Surface Treatment: Anodize  Screw Surface Treatment Specification: Mil-a-8625 military specification single treatment response  Head Hole Configuration Style: Round
Head Diameter:  Between 0.292 inches and 0.313 inches  Head Height:  Between 0.123 inches and 0.130 inches  Internal Drive Style:  Slot  Thread Diameter: 0.190 inches  Hole Quantity: 1  Thready Qty Per Inch (tpi): 32  Min. Tensile Strength (psi): 62000 pounds per square inch  Screw Material: Aluminum alloy 2024  Screw Material Specification: Qq-a-225/6 federal specification single material response  Screw Surface Treatment: Anodize  Screw Surface Treatment Specification: Mil-a-8625 military specification single treatment response  Head Hole Configuration Style: Round
Between 0.292 inches and 0.313 inches  Head Height:  Between 0.123 inches and 0.130 inches  Internal Drive Style:  Slot  Thread Diameter: 0.190 inches  Hole Quantity: 1  Thready Qty Per Inch (tpi): 32  Min. Tensile Strength (psi): 62000 pounds per square inch  Screw Material:  Aluminum alloy 2024  Screw Material Specification:  Qq-a-225/6 federal specification single material response  Screw Surface Treatment:  Anodize  Screw Surface Treatment Specification:  Mil-a-8625 military specification single treatment response  Head Hole Configuration Style:  Round
Head Height: Between 0.123 inches and 0.130 inches Internal Drive Style: Slot Thread Diameter: 0.190 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 62000 pounds per square inch Screw Material: Aluminum alloy 2024 Screw Material Specification: Qq-a-225/6 federal specification single material response Screw Surface Treatment: Anodize Screw Surface Treatment Specification: Mil-a-8625 military specification single treatment response Head Hole Configuration Style: Round
Between 0.123 inches and 0.130 inches Internal Drive Style: Slot Thread Diameter: 0.190 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 62000 pounds per square inch Screw Material: Aluminum alloy 2024 Screw Material Specification: Qq-a-225/6 federal specification single material response Screw Surface Treatment: Anodize Screw Surface Treatment Specification: Mil-a-8625 military specification single treatment response Head Hole Configuration Style: Round
Internal Drive Style: Slot Thread Diameter: 0.190 inches Hole Quantity: 1 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 62000 pounds per square inch Screw Material: Aluminum alloy 2024 Screw Material Specification: Qq-a-225/6 federal specification single material response Screw Surface Treatment: Anodize Screw Surface Treatment Specification: Mil-a-8625 military specification single treatment response Head Hole Configuration Style: Round
Thread Diameter:  0.190 inches  Hole Quantity:  1  Thready Qty Per Inch (tpi):  32  Min. Tensile Strength (psi): 62000 pounds per square inch  Screw Material:  Aluminum alloy 2024  Screw Material Specification:  Qq-a-225/6 federal specification single material response  Screw Surface Treatment:  Anodize  Screw Surface Treatment Specification:  Mil-a-8625 military specification single treatment response  Head Hole Configuration Style:  Round
Thread Diameter:  0.190 inches  Hole Quantity:  1  Thready Qty Per Inch (tpi):  32  Min. Tensile Strength (psi): 62000 pounds per square inch  Screw Material:  Aluminum alloy 2024  Screw Material Specification:  Qq-a-225/6 federal specification single material response  Screw Surface Treatment:  Anodize  Screw Surface Treatment Specification:  Mil-a-8625 military specification single treatment response  Head Hole Configuration Style:  Round
0.190 inches  Hole Quantity:  1  Thready Qty Per Inch (tpi):  32  Min. Tensile Strength (psi): 62000 pounds per square inch Screw Material:  Aluminum alloy 2024  Screw Material Specification:  Qq-a-225/6 federal specification single material response Screw Surface Treatment:  Anodize  Screw Surface Treatment Specification:  Mil-a-8625 military specification single treatment response  Head Hole Configuration Style:  Round
Hole Quantity:  1 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 62000 pounds per square inch Screw Material: Aluminum alloy 2024 Screw Material Specification: Qq-a-225/6 federal specification single material response Screw Surface Treatment: Anodize Screw Surface Treatment Specification: Mil-a-8625 military specification single treatment response Head Hole Configuration Style: Round
Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 62000 pounds per square inch Screw Material: Aluminum alloy 2024 Screw Material Specification: Qq-a-225/6 federal specification single material response Screw Surface Treatment: Anodize Screw Surface Treatment Specification: Mil-a-8625 military specification single treatment response Head Hole Configuration Style: Round
Thready Qty Per Inch (tpi):  32  Min. Tensile Strength (psi): 62000 pounds per square inch Screw Material: Aluminum alloy 2024 Screw Material Specification: Qq-a-225/6 federal specification single material response Screw Surface Treatment: Anodize Screw Surface Treatment Specification: Mil-a-8625 military specification single treatment response Head Hole Configuration Style: Round
Min. Tensile Strength (psi): 62000 pounds per square inch Screw Material: Aluminum alloy 2024 Screw Material Specification: Qq-a-225/6 federal specification single material response Screw Surface Treatment: Anodize Screw Surface Treatment Specification: Mil-a-8625 military specification single treatment response Head Hole Configuration Style: Round
Min. Tensile Strength (psi): 62000 pounds per square inch Screw Material: Aluminum alloy 2024 Screw Material Specification: Qq-a-225/6 federal specification single material response Screw Surface Treatment: Anodize Screw Surface Treatment Specification: Mil-a-8625 military specification single treatment response Head Hole Configuration Style: Round
62000 pounds per square inch  Screw Material: Aluminum alloy 2024  Screw Material Specification: Qq-a-225/6 federal specification single material response Screw Surface Treatment: Anodize  Screw Surface Treatment Specification: Mil-a-8625 military specification single treatment response  Head Hole Configuration Style: Round
Screw Material: Aluminum alloy 2024 Screw Material Specification: Qq-a-225/6 federal specification single material response Screw Surface Treatment: Anodize Screw Surface Treatment Specification: Mil-a-8625 military specification single treatment response Head Hole Configuration Style: Round
Aluminum alloy 2024  Screw Material Specification:  Qq-a-225/6 federal specification single material response  Screw Surface Treatment:  Anodize  Screw Surface Treatment Specification:  Mil-a-8625 military specification single treatment response  Head Hole Configuration Style:  Round
Screw Material Specification:  Qq-a-225/6 federal specification single material response  Screw Surface Treatment:  Anodize  Screw Surface Treatment Specification:  Mil-a-8625 military specification single treatment response  Head Hole Configuration Style:  Round
Qq-a-225/6 federal specification single material response  Screw Surface Treatment:  Anodize  Screw Surface Treatment Specification:  Mil-a-8625 military specification single treatment response  Head Hole Configuration Style:  Round
Screw Surface Treatment: Anodize Screw Surface Treatment Specification: Mil-a-8625 military specification single treatment response Head Hole Configuration Style: Round
Anodize  Screw Surface Treatment Specification:  Mil-a-8625 military specification single treatment response  Head Hole Configuration Style:  Round
Screw Surface Treatment Specification:  Mil-a-8625 military specification single treatment response  Head Hole Configuration Style:  Round
Mil-a-8625 military specification single treatment response  Head Hole Configuration Style:  Round
Head Hole Configuration Style: Round
Round
Thread Series Designator:
Unf
Departure From Cited Designator:
As modified by material
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5305-00-455-3319

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-a-8625 spec.