

View Online at <https://aerobasegroup.com/nsn/5305-00-455-6995>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.266 inches and 0.296 inches

**Fastener Length:**

Between 0.485 inches and 0.515 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.297 inches and 0.327 inches

**Head Height:**

Between 0.085 inches and 0.115 inches

**First Diameter From Head:**

Between 0.184 inches and 0.186 inches

**Second Diameter From Head:**

0.097 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.079 inches and 0.110 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 0.149 inches and 0.189 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

2

**Material:**

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 322 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

**Material Specification:**

66 federal standard all material responses

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35, type 2 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0