NSN 5305-00-455-7450

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-455-7450 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.835 inches and 0.928 inches **Fastener Length:** Between 0.969 inches and 1.000 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.285 inches and 0.332 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 62000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Aluminum alloy 2024 **Screw Material Specification:** Qq-a-225/6 federal specification single material response **Screw Surface Treatment:** Anodize **Screw Surface Treatment Specification:** Mil-a-8625, type 1 military specification single treatment response or mil-a-8625, type 2 military specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 3 type and 3c style **Departure From Cited Designator:** As mod by matl Shelf Life:

Demilitarization:

Unit Of Measure:

N/a

No

NSN 5305-00-455-7450

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-a-8625 spec.