## NSN 5305-00-456-2477

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-456-2477

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.919 inches and 1.000 inches
Fastener Length:
Between 0.969 inches and 1.000 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.178 inches and 0.183 inches
Head Height:
Between 0.059 inches and 0.069 inches
Hole Diameter:
0.038 inches
Internal Drive Style:
Torque set
Thread Diameter:
0.112 inches
Hole Quantity:
2
Thready Qty Per Inch (tpi):
40
Min. Tensile Strength (psi):
140000 pounds per square inch
Hardness Rating:
Between 248.0 brinell standard and 341.0 brinell standard
Screw Material:
Iron alloy 660
Screw Material Specification:
Ams 5732 assn standard single material response
Ams 5732 assn standard single material response  Screw Surface Treatment:
Screw Surface Treatment:
Screw Surface Treatment: Passivate
Screw Surface Treatment:  Passivate  Screw Surface Treatment Specification:
Screw Surface Treatment:  Passivate  Screw Surface Treatment Specification:  Qq-p-35 federal specification single treatment response
Screw Surface Treatment:  Passivate  Screw Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Head Hole Configuration Style:
Screw Surface Treatment:  Passivate  Screw Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Head Hole Configuration Style:  Round
Screw Surface Treatment:  Passivate  Screw Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Head Hole Configuration Style:  Round  Thread Series Designator:

## NSN 5305-00-456-2477

Machine Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A500d0