

View Online at <https://aerobasegroup.com/nsn/5305-00-456-7841>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.260 inches and 0.280 inches

**Fastener Length:**

Between 0.740 inches and 0.760 inches

**Head Style:**

Flat countersunk undercut

**Head Diameter:**

Between 0.191 inches and 0.225 inches

**Head Height:**

0.049 inches

**First Diameter From Head:**

0.090 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.460 inches and 0.500 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Stainless steel or steel

**Material Specification:**

Qq-s-763, 300 series federal specification 1st material response or 66, 300 series federal standard 1st material response or comp 16-18 or 18-8 assn standard 2nd material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-f-14072, finish e300 military specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-f-14072 spec.