## NSN 5305-00-456-7841

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-456-7841 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.260 inches and 0.280 inches **Fastener Length:** Between 0.740 inches and 0.760 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.191 inches and 0.225 inches **Head Height:** 0.049 inches **First Diameter From Head:** 0.090 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.460 inches and 0.500 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Externally Relieved Body Diameter Quantity:** Material: Stainless steel or steel **Material Specification:** Qq-s-763, 300 series federal specification 1st material response or 66, 300 series federal standard 1st material response or comp 16-18 or 18-8 assn standard 2nd material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life:

--

N/a

**Unit Of Measure:** 

## NSN 5305-00-456-7841

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.