# NSN 5305-00-458-1624

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-458-1624

Thread	Class:

2a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

0.375 inches

## Fastener Length:

0.375 inches

#### **Head Style:**

Fillister

#### Head Diameter:

Between 0.083 inches and 0.096 inches

### **Head Height:**

Between 0.029 inches and 0.038 inches

### Internal Drive Style:

Slot

### Thread Diameter:

0.060 inches

## Thready Qty Per Inch (tpi):

80

## Min. Tensile Strength (psi):

70000 pounds per square inch

## Hardness Rating:

Between 80.0 rockwell b and 85.0 rockwell b

## Screw Material:

Steel comp 303

### **Screw Material Specification:**

Qq-s-764 cond a federal specification single material response

### Screw Surface Treatment:

Passivate

## Screw Surface Treatment Specification:

Mil-t-704 military specification single treatment response

### **Thread Series Designator:**

Unf

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A500d0

## NSN 5305-00-458-1624

Machine Screw - Page 2 of 2

Mil-std (military Standard):

Mil-t-704 spec.

