NSN 5305-00-458-1655

Thumbscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-458-1655 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.170 inches and 0.190 inches **Fastener Length:** Between 0.700 inches and 0.720 inches **Head Style:** Knurled no. 1 **Head Diameter:** 0.380 inches **Head Height:** Between 0.280 inches and 0.300 inches **Shoulder Diameter:** 0.250 inches first shoulder **Shoulder Length:** 0.020 inches first shoulder **Point Style: Pointless Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Shoulder Shape:** Round first shoulder **Product Name:** Navy special project **Special Features:** Unthreaded portion of shank undercut to 0.116 dia Material: Steel comp 303 **Material Specification:** Qq-s-764 federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc

Shelf Life: N/a

NSN 5305-00-458-1655

Thumbscrew - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0