## NSN 5305-00-458-2254

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-458-2254 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.609 inches and 0.641 inches **Fastener Length:** Between 1.546 inches and 1.578 inches **Head Style:** Hexagon **Head Height:** Between 0.187 inches and 0.251 inches Width Between Flats: Between 0.546 inches and 0.578 inches **First Diameter From Head:** Between 0.224 inches and 0.244 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.905 inches and 0.969 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## NSN 5305-00-458-2254

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0