NSN 5305-00-459-7401

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-459-7401
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.359 inches and 0.391 inches
Fastener Length:
Between 1.172 inches and 1.203 inches
Head Style:
Knurled no. 1
Head Diameter:
Between 0.745 inches and 0.755 inches
Head Height:
Between 0.234 inches and 0.266 inches
First Diameter From Head:
Between 0.170 inches and 0.180 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.783 inches and 0.844 inches
Internal Drive Style:
Slot
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
20
Externally Relieved Body Diameter Quantity:
1
Product Name:
Navy special project
Material:
Steel comp 303
Material Specification:
Astm a582 assn standard single material response
Surface Treatment:
Passivate
Special Test Features:
Special quality control testing
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Test Data Document:
81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

NSN 5305-00-459-7401

Externally Relieved Body Screw - Page 2 of 2



Reference Number Differentiating Characteristics:

As differentiated by material which must conform to ships parts control center special quality control provisions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0