

View Online at <https://aerobasegroup.com/nsn/5305-00-460-0707>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.395 inches and 0.496 inches

Fastener Length:

Between 0.936 inches and 0.976 inches

Head Style:

Pan

Head Diameter:

Between 0.671 inches and 0.709 inches

Head Height:

Between 0.191 inches and 0.215 inches

Shoulder Diameter:

0.371 inches first shoulder and 0.374 inches first shoulder

Shoulder Length:

0.438 inches first shoulder and 0.458 inches first shoulder

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.312 inches

Thread Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

Shoulder Shape:

Round first shoulder

Material:

Steel comp 8630 or steel comp 4037

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification all treatment responses

Thread Series Designator:

Unf

Specification Data:

80205-nas1298 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0