## NSN 5305-00-460-0707

Shoulder Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-460-0707



## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.395 inches and 0.496 inches Fastener Length: Between 0.936 inches and 0.976 inches **Head Style:** Pan **Head Diameter:** Between 0.671 inches and 0.709 inches **Head Height:** Between 0.191 inches and 0.215 inches **Shoulder Diameter:** 0.371 inches first shoulder and 0.374 inches first shoulder Shoulder Length: 0.438 inches first shoulder and 0.458 inches first shoulder **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Steel comp 8630 or steel comp 4037 Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification all treatment responses **Thread Series Designator:** Unf **Specification Data:** 80205-nas1298 professional/industrial association standard Shelf Life: N/a

## NSN 5305-00-460-0707

Shoulder Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

