NSN 5305-00-461-5632

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-461-5632 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.304 inches and 0.336 inches **Fastener Length:** Between 0.484 inches and 0.516 inches **Head Style:** Fillister **Head Diameter:** Between 0.245 inches and 0.250 inches **Head Height:** 0.106 inches **First Diameter From Head:** Between 0.115 inches and 0.120 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.180 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Hardness Rating:** 34.0 rockwell c and 38.0 rockwell c **Externally Relieved Body Diameter Quantity:** Material: Steel comp 8740 **Material Specification:** Mil-s-6049 cond c-4 military specification single material response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A003b0

NSN 5305-00-461-5632

Externally Relieved Body Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6049 spec.