Externally Relieved Body Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-462-0206

| Thread Class:   |  |
|---|--|
| 2a  |  |
| Thread Direction:   |  |
| Right-hand  |  |
| Thread Length:  |  |
| Between 0.278 inches and 0.298 inches                                   |  |
| Fastener Length:  |  |
| Between 0.830 inches and 0.910 inches                                   |  |
| Head Style:   |  |
| Knurled no. 1   |  |
| Head Diameter:  |  |
| Between 0.311 inches and 0.314 inches                                   |  |
| Head Height:  |  |
| Between 0.270 inches and 0.350 inches                                   |  |
| First Diameter From Head:   |  |
| Between 0.095 inches and 0.100 inches                                   |  |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |  |
| Between 0.490 inches and 0.510 inches                                   |  |
| Internal Drive Style:   |  |
| Slot  |  |
| Thread Diameter:  |  |
| 0.164 inches  |  |
| Thready Qty Per Inch (tpi):   |  |
| 32  |  |
| Externally Relieved Body Diameter Quantity:                             |  |
| 1   |  |
| Special Features:   |  |
| 90 degrees cone point   |  |
| Material:   |  |
| Stainless steel   |  |
| Thread Series Designator:   |  |
| Unc   |  |
| Shelf Life:   |  |
| N/a   |  |
| Unit Of Measure:  |  |
|   |  |
| Demilitarization:   |  |
| No  |  |
| Fiig:   |  |
| A003b0  |  |
|   |  |
|   |  |