

View Online at <https://aerobasegroup.com/nsn/5305-00-463-0411>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.280 inches and 0.361 inches

Fastener Length:

Between 0.862 inches and 0.902 inches

Head Style:

Hexagon

Head Height:

Between 0.109 inches and 0.141 inches

Width Between Flats:

Between 0.365 inches and 0.377 inches

Shoulder Diameter:

0.186 inches first shoulder and 0.189 inches first shoulder

Shoulder Length:

0.510 inches first shoulder and 0.520 inches first shoulder

Internal Drive Style:

W/o internal drive

Thread Diameter:

0.138 inches

Thread Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

Shoulder Shape:

Round first shoulder

Material:

Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification all treatment responses

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0