NSN 5305-00-465-5445

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-465-5445 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** Between 0.677 inches and 0.697 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.370 inches and 0.380 inches **Head Height:** Between 0.422 inches and 0.454 inches **First Diameter From Head:** Between 0.125 inches and 0.135 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.271 inches and 0.291 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Nonstandard point no. 6, 0.156 in. Lg, 0.130 in. Dia, 90.0 degree angle Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

Unit Of Measure:

NSN 5305-00-465-5445

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0