NSN 5305-00-467-7554

Close Tolerance Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-467-7554

| Thread Olara |
|--|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.220 inches |
| Fastener Length: |
| Between 0.683 inches and 0.703 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.337 inches and 0.387 inches |
| Grip Diameter: |
| Between 0.1898 inches and 0.1904 inches |
| Internal Drive Style: |
| High-torque |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 0.400 inches and 0.463 inches |
| Thready Qty Per Inch (tpi): |
| 32a |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Material: |
| Titanium alloy uns r56400 |
| Material Specification: |
| Ams 4967 assn standard single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Std 2167 cagec 99995 mfr ref single treatment response |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |
| Fiig: |
| A003b0 |