## NSN 5305-00-469-3535

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-469-3535 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.267 inches and 0.334 inches **Fastener Length:** Between 0.777 inches and 0.824 inches **Head Style:** Flat countersunk **Head Diameter:** 0.507 inches **Grip Diameter:** Between 0.2483 inches and 0.2492 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 0.46 rockwell c and 50.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads Material: Steel comp h11 **Material Specification:** Ams6485 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Nas 672 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

## NSN 5305-00-469-3535

Close Tolerance Screw - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0