

View Online at <https://aerobasegroup.com/nsn/5305-00-469-3686>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.500 inches

Fastener Length:

Between 0.469 inches and 0.500 inches

Head Style:

Hexagon

Head Height:

Between 0.150 inches and 0.163 inches

Width Between Flats:

Between 0.428 inches and 0.438 inches

Shank Unthreaded Hole Diameter:

0.074 inches first hole and 0.082 inches first hole

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

120000 pounds per square inch

Hardness Rating:

25.0 rockwell c and 34.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.350 inches first hole and 0.401 inches first hole

Surface Finish:

63.0 microinches threads

Material:

Steel

Material Specification:

Sae gr 5 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification all treatment responses

Thread Series Designator:

Unc

Specification Or Standard:

2 type and 10p style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0