NSN 5305-00-469-4467

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-469-4467 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.628 inches and 1.750 inches **Fastener Length:** Between 1.690 inches and 1.750 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Primary Washer Outside Diameter:** 1.625 inches **Primary Washer Style:** Flat **Primary Washer Material Thickness:** 0.300 inches Material: Stainless steel primary washer **Material Specification:** Mil-s-5626, cond f military specification single material response primary washer **Surface Treatment:** Cadmium fastener **Surface Treatment Specification:** Qq-p-416, type 2 federal specification single treatment response fastener

Unf

Thread Series Designator:

NSN 5305-00-469-4467

Assembled Washer Screw - Page 2 of 2



N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Shelf Life:

Mil-std (military Standard): Mil-s-6050 spec.