

View Online at <https://aerobasegroup.com/nsn/5305-00-470-1560>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.688 inches and 0.750 inches

Fastener Length:

Between 0.719 inches and 0.750 inches

Head Style:

Pan

Head Diameter:

Between 0.306 inches and 0.322 inches

Head Height:

Between 0.105 inches and 0.115 inches

Internal Drive Style:

Torque set

Thread Diameter:

0.164 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

Between 36.0 rockwell c and 40.0 rockwell c

Screw Material:

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

Screw Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response

Screw Surface Treatment:

Cadmium and chromate

Screw Surface Treatment Specification:

Qq-p-416, type 2 cl 3 federal specification all treatment responses

Color:

Black

Thread Series Designator:

Unc

Specification Data:

80205-nas1100 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0

Mil-std (military Standard):

Mil-s-5626 spec.