## NSN 5305-00-470-5600

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-470-5600 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.312 inches **Fastener Length:** Between 1.360 inches and 1.392 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.359 inches and 0.391 inches **Head Height:** Between 0.422 inches and 0.454 inches **First Diameter From Head:** Between 0.125 inches and 0.135 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.953 inches and 0.985 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 115000 pounds per square inch Minimum Yield Strength: 30000 pounds per square inch **Externally Relieved Body Diameter Quantity: Special Features:** Cone point Material: Steel comp 302 **Material Specification:** Qq-s-763 federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** 171, finish no. 5.4.1 military standard single treatment response

Unf

**Thread Series Designator:** 

## NSN 5305-00-470-5600

Externally Relieved Body Screw - Page 2 of 2



Sneir	Lite:
N/a	

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0