NSN 5305-00-470-5601

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-470-5601 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.140 inches and 0.210 inches **Fastener Length:** Between 0.440 inches and 0.470 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **First Diameter From Head:** Between 0.133 inches and 0.143 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.260 inches and 0.300 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 1010 or steel comp 1011 or steel comp 1013 **Material Specification:** Aisi assn standard all material responses **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification all treatment responses **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-00-470-5601

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0