## NSN 5305-00-470-5798

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-470-5798



**Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.001 inches and 1.125 inches **Fastener Length:** Between 1.063 inches and 1.125 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.265 inches and 0.275 inches **Head Height:** Between 0.088 inches and 0.102 inches **Locking Feature:** Strip threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 140000 pounds per square inch Hardness Rating: 248.0 brinell standard and 341.0 brinell standard Surface Finish: 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams 5735 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1191 professional/industrial association standard

N/a

Shelf Life:

## NSN 5305-00-470-5798

Socket Head Cap Screw - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0