Socket Head Cap Screw - Page 1 of 2





View Online at https://aerobasegroup.com/nsn/5305-00-470-5988

٦	hread Class:
3	a
٦	hread Direction:
F	Right-hand
٦	Thread Length:
E	Between 0.323 inches and 0.381 inches
F	astener Length:
E	Between 0.359 inches and 0.381 inches
ŀ	lead Style:
F	Tat chamfer
ŀ	lead Diameter:
E	Between 0.134 inches and 0.140 inches
ł	lead Height:
E	Between 0.083 inches and 0.086 inches
I	nternal Drive Style:
H	lexagon
٦	hread Diameter:
C	0.086 inches
١	Vidth Across Flats:
E	Between 0.078 inches and 0.079 inches
٦	hready Qty Per Inch (tpi):
5	6
Γ	/lin. Tensile Strength (psi):
8	30000 pounds per square inch
ł	lardness Rating:
8	30.0 rockwell b
	Ainimum Yield Strength:
	00000 pounds per square inch
C	Color:
E	Black
	/aterial:
	Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316
	Interial Specification:
	6 federal standard all material responses
ę	Surface Treatment:
	Dxide
٦	hread Series Designator:
	Jnc
S	Specification Or Standard:
6	type
ę	Shelf Life:
١	N/a

NSN 5305-00-470-5988

Socket Head Cap Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

