NSN 5305-00-472-2424

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-472-2424 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.390 inches **Fastener Length:** 0.560 inches **Head Style:** Knurled no. 1 **Head Diameter:** 0.625 inches **Head Height:** 0.250 inches **First Diameter From Head:** Between 0.305 inches and 0.310 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.120 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Hardness Rating: 50.0 rockwell c and 55.0 rockwell c **Externally Relieved Body Diameter Quantity: Special Features:** Half dog point 0.305 in. Min 0.310 in. Maximum diameter 0.050 in. Min 0.070 in. Maximum Ig Material: Steel comp 4140 **Material Specification:** Qq-s-624 federal specification single material response **Surface Treatment:** Cadmium **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-00-472-2424

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0