NSN 5305-00-472-2839

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-472-2839 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.375 inches **Fastener Length:** Between 1.335 inches and 1.355 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.359 inches and 0.391 inches **Head Height:** Between 0.422 inches and 0.454 inches **First Diameter From Head:** Between 0.120 inches and 0.130 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.865 inches and 0.895 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Cone point 90 degree angle Material: Steel comp 302 **Material Specification:** Qq-s-763 federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** 171, finish no. 5.4.1 military standard single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-00-472-2839

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0